Fire Classifications to EN357 Explained

E & El Ratings represent products such as Steel, Aluminium and Glass which are conductors of heat
FD Ratings represent products such as Timber which are non-conductors of heat

iSteel specialise is Glazed Steel products, which is why we offer 'E' & 'El' Fire Ratings. To ensure the correct product is quoted for and ultimately installed, we recommend presenting this information to your local Building Control for confirmation of the level of rating your project requires.

E (Integrity Only)

Integrity Only Fire Raating refers to the length of time the product will prevent the passage of flames from transfering from the fire side, But offers no protection against heat.

An 'E' rating is followed by a number, which indicates the number of minutes the product will sustain protection for.

Typical 'E' Ratings

E30 (30/0) = 30 Minutes E60 (60/0) = 60 Minutes E90 (90/0) = 90 Minutes E120 (120/0) = 120 Minutes

El (Integrity & Insulation)

Integrity & Insulation Fire Raating refers to the length of time the product will prevent the passage of flames, smoke and heat from transfering from the fire side.

An 'EI' rating is followed by a number, which indicates the number of minutes the product will sustain protection for.

Typical 'El' Ratings

EI30 (30/30) = 30 Minutes EI60 (60/60) = 60 Minutes EI90 (90/90) = 90 Minutes EI120 (120/120) = 120 Minutes



www.isteel.co.uk T: 0330 1331 069 E: sales@isteel.co.uk